



# STA-ZORB

## Super Absorbent!

### SOAKS UP LIQUIDS IN ONE EASY SWEEP!

#### **Absorbs like a sponge!**

Sta-Zorb's fast-acting special ingredient, Liqui-Zorb, soaks up all kinds of liquids...oil, water, grease, coffee and paint. Absorbs flammable and hazardous liquid immediately leaving only the solid material to dispose of by sweeping or shoveling into drums. Use in any area, any location!

#### **Eliminates dangerous conditions**

Most safety data sheets require cleanup of hazardous spills with an absorbent. Always keep a drum of Sta-Zorb on hand to absorb accidental spills. Eliminates any spilled liquid that could cause dangerous slippery and skidding conditions. Prevents falling accidents. Also, fireproof and unaffected by heat or cold; harmless to skin, clothing and equipment.

#### **Leaves surfaces clean and dry**

Contains no sawdust to leave a dusty residue. Cleans all types of spills in one easy sweep. Goes to work immediately; keeps on working until every grain is thoroughly saturated. Surfaces remain clean and dry. Produces no dusting, mudding or caking.



Use Sta-Zorb when its most needed!

- Airports
- Chemical Plants
- Farms
- Garages
- Hotels/Motels
- Lubrication Shops
- Machine Shops
- Manufacturing Plants
- Meat Packing & Poultry Plants
- Municipal
- Parking Lots
- Railroad Yards
- Restaurants
- Schools
- Service Stations
- Ships
- Shopping Centers
- Storage Areas
- Tire Shops
- Truck Depots
- Warehouses



# STA-ZORB

## Super Absorbent!

### **DIRECTIONS:**

Spread a layer about 1/4" thick on the spill. Allow to react for 1 to 2 minutes. For more resistant spills, allow a longer period of time. Brush or sweep off the area.

### **TECHNICAL DATA:**

**Free Moisture:** 4%

**Total Moisture:** 9%

#### **Van Trump Test:**

Oil Absorption: 120%

Oil & Water: 128%

Water: 140%

**Calcination:** 99%

**Hardness:** 87%

**Resistance to Attrition:** 2.2 thru 80 mesh

**Density Free Fall:** 28 to 31 lbs.

#### **LBS./CU. FT.**

**Dust Multiple:** 3

#### **Screen Analysis:**

On 6	0	Thru 20 on 30	4.6
Thru 6 on 8	4.6	Thru 30 on 40	3.2
Thru 8 on 10	27.4	Thru 40 on 60	1.5
Thru 10 on 20	58.1	Thru 60 on Pan	0.5

#### **Chemical Analysis:**

SiO <sub>2</sub>	72.00%	K <sub>2</sub> O	0.35%
Al <sub>2</sub> O <sub>3</sub>	18.35%	MgO	0.28%
Fe <sub>2</sub> O <sub>3</sub>	2.38%	CaO	0.68%
TiO <sub>2</sub>	0.47%		

**Loss on Ignition 1000 degrees Centigrade:** 5.64%

**pH Factor:** 5.6

**ICC Classification:** Ground Clay, NOIBN

#### **Packaging:**

37070

250lb. Drum



**State Chemical**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.statechemical.com

**Canada**  
1745 Meyerside Drive, Unit #1  
Mississauga, Ontario L5T 1C6  
To Order Call: 1-800-668-6513

State Chemical is a Division of State Industrial Products, Corp.